



# INSTALLATION INSTRUCTIONS

Accessory

FULL NOSE MASK  
P/N 08P35-SVB-100

Application

2006-2008 CIVIC 2-DOOR ST

Publications No.

All 37841


Issue Date

SEP 2007


Put this information in the glove box with the vehicle owner's manual.

## PARTS LIST

Mask  
(hood section)



Mask  
(bumper section)



2 Snap-screws (A)



2 Washers



2 Fenderwell nuts




2 Clips




2 Snap-screws (B)



Elastic cord



Storage bag



## TOOLS AND SUPPLIES REQUIRED

Stubby Phillips screwdriver

Flat-tip screwdriver

Scissors

## INSTALLATION


### NOTE:

- Make sure the vehicle and the nose mask are clean and completely dry before installation. If moisture under the mask is allowed to dry, it may cloud the paint. If the mask gets wet, remove it and allow it to air-dry completely.
- Make sure any repainted surfaces are cured.
- Make sure the hood and nose of the vehicle have been waxed with a high-quality paste wax.
- Make sure to install the nose mask securely. If the nose mask starts to flap or comes loose while driving, safely pull off the highway, stop the vehicle, and secure or remove the mask.

### Displaying the Front License Plate


If your state law requires the display of both license plates, cut out the piece of the bumper section that covers the front license plate:

- Face the inside of the mask towards you.
- Carefully cut out the license plate section with scissors at the top seam, and remove the overcast stitching.




### Installing the Hood Section

1. Open the hood. Fit the corners of the mask around the hood. Adjust the mask so that it fits smoothly over the edges. Attach the "S" hooks to the hood.




### Installing the Fender Section

2. Remove the clip from the left front fender.



3. Install one new clip with a snap-screw (B) into the hole where you removed the clip, and tighten the snap-screw (B).



4. Repeat steps 2 and 3 to install a snap-screw (B) on the right side of the vehicle.





