



INSTALLATION INSTRUCTIONS

Accessory

FULL NOSE MASK
P/N 08P35-T0A-100A

Application

2016 CR-V

Publications No.


VERSION 1

Issue Date


SEP 2015

PARTS LIST


Mask
(hood section)



Mask
(bumper section)




Storage bag



TOOLS AND SUPPLIES REQUIRED

Scissors

Illustration of the Full Nose Mask Installed on the Vehicle



INSTALLATION

Customer Information: The information in this installation instruction is intended for use only by skilled technicians who have the proper tools, equipment, and training to correctly and safely add equipment to your vehicle. These procedures should not be attempted by “do-it-yourselfers.”


NOTE:

- Make sure the vehicle and nose mask are clean and completely dry before installation. If moisture under the mask is allowed to dry, it may cloud the paint. If the mask gets wet, remove and allow it to air-dry completely.
- Make sure any repainted surfaces are cured.
- Make sure the hood and nose of the vehicle have been waxed with a high-quality paste wax.
- Make sure to install the nose mask securely. If the nose mask starts to flap or comes loose while driving, safely pull to the side of the road, stop the vehicle, and secure or remove the nose mask.

Displaying the License Plate

If your state law requires the display of both license plates, cut out the piece of the bumper section that covers the front license plate:

- Face the inside of the mask toward you.
- Carefully cut out the overcast stitching with scissors. Remove the stitching and license plate section.




QA71011AB

With Fog Lights

If the vehicle is equipped with the fog lights, cut out the piece of the bumper section that covers the fog lights:

- Face the inside of the mask toward you.
- Carefully cut out the overcast stitching with scissors. Remove the stitching and fog light section.




QD12103BC

Installing the Hood Section

1. Open the hood. Fit the corners of the mask (hood section) around the hood. Adjust the mask so that it fits smoothly over the edges. Attach six hooks to the hood.

Do not fold back the rubber seal inside the hood when installing the hook.


Remove / install the hooks by inserting your finger into the belt of each hook. Pulling the hooks with excessive force can break the hook strap.




QD12104BC

Installing the Bumper Section


2. Attach two hooks to the inside edge of the front grille as shown.




3. Insert four tabs under the left headlight. Repeat on the right side.




4. Attach three hooks to the inside edge of the front bumper. Repeat on the right side.



5. Attach one hook to the hole on the front bumper. Repeat on the right side.



6. Attach five plastic hooks to the fenderwell. Repeat on the right side.



CLEANING THE NOSE MASK

Use a sponge or cloth and a solution of mild liquid dishwashing soap and water to clean the vinyl and the flannel backing. Rinse the mask completely with clean water, and hang it to dry out of direct sunlight. Make sure the mask is completely dry before you reinstall it.