






SAFETY DATA SHEET

Product Name:	PPE
Honda Power Steering Fluid, 12 x 12oz. Case	  

Revision Date: 24-May-2017

Revision Number: 1

1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

1.1 Product Identifier

Product Name: Honda Power Steering Fluid, 12 x 12oz. Case

Other means of identification

Product Code: 34051027-97200C020

Synonyms Not available

1.2 Recommended use of the chemical and restrictions on use

Recommended Use Automotive Lubricant

Uses advised against No information available

1.3. Details of the supplier of the safety data sheet

Manufactured by Idemitsu Lubricants America Corporation, 701 Port Rd., Jeffersonville, IN. 47130 Telephone: 812-285-8234, Fax: 812-285-8243, Contact Name: Robin Hutchens, Email: sds@ilacorp.com

24 Hour Emergency Phone Number: Within USA and Canada: 1 800-424-9300
Outside USA and Canada: + 1 703-741-5970 (collect calls accepted)

2. HAZARDS IDENTIFICATION

2.1 Classification

This material is considered hazardous by the 2012 OSHA Hazard Communication Standard (29 CFR 1910.1200) and WHMIS 2015

Acute toxicity - Oral	Not classified
Acute toxicity - Dermal	Not classified
Acute Toxicity - Inhalation (Gases)	Not classified
Acute Toxicity - Inhalation (Vapors)	Not classified
Acute Toxicity - Inhalation (Dusts/Mists)	Not classified
Skin corrosion/irritation	Not classified
Serious eye damage/eye irritation	Not classified
Respiratory sensitization	Not classified
Skin sensitization	Category 1
Germ cell mutagenicity	Not classified
Carcinogenicity	Not classified
Reproductive toxicity	Not classified
Specific target organ toxicity (single exposure)	Not classified
Specific target organ toxicity (repeated exposure)	Not classified
Aspiration toxicity	Not classified
Physical Hazards	Not classified
Physical Hazards	None

2.2. Label elements



Signal word

Warning

Hazard statements

H317 - May cause an allergic skin reaction

Precautionary Statements - Prevention:

P261 - Avoid breathing dust, fume, gas, mist, vapors or spray
P280 - Wear protective gloves
P272 - Contaminated work clothing should not be allowed out of the workplace

Precautionary Statements - Response:

P321 - Specific treatment (see supplemental first aid instructions on this label)
P362 + P364 - Take off all contaminated clothing and wash it before reuse

Skin

P302 + 352 - IF ON SKIN: Wash with plenty of soap and water
P363 - Wash contaminated clothing before reuse
P333 + P313 - If skin irritation or rash occurs: Get medical advice/attention

Precautionary Statements - Disposal:

P501 - Dispose of contents/ container to an approved waste disposal plant

Hazards not otherwise classified (HNOC)

Not applicable

2.3 Other information

Other hazards

- May be harmful in contact with skin
- Harmful to aquatic life
- Harmful to aquatic life with long lasting effects

Unknown acute toxicity

17.22 % of the mixture consists of ingredient(s) of unknown toxicity

3. COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substances

Not applicable

3.2 Mixtures

Hazardous Components

Chemical Name	CAS No.	Weight-%	US GHS Classification	Notes
Methyl methacrylate	80-62-6	<1	STOT SE 3 (H335) Skin Irrit. 2 (H315) Skin Sens. 1 (H317)	D

Non-Hazardous Components

Chemical Name	CAS No.	Weight-%
Lubricating Base Stocks	Mixture	80-90

4. FIRST AID MEASURES

4.1 4.1 First Aid Measures

General Advice

If symptoms persist, call a physician. Take a copy of the Safety Data Sheet when going for medical treatment.

Eye Contact

Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Keep eye wide open while rinsing. If eye irritation persists: Get medical advice/attention.

Skin Contact

Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Wash contaminated clothing before re-use. Call a physician immediately.

Inhalation

Move to fresh air in case of accidental inhalation of vapors. If breathing is difficult, give oxygen. If not breathing, give artificial respiration. Call a physician immediately.

Ingestion

Do not induce vomiting without medical advice. If vomiting occurs naturally, have casualty lean forward to reduce the risk of aspiration. If symptoms persist, call a physician.

Protection of First-aiders

Use personal protective equipment. Avoid contact with eyes, skin and clothing.

4.2 4.2 Most important symptoms and effects, both acute and delayed

Symptoms

No information available.

4.3 4.3 Indication of any immediate medical attention and special treatment needed

Notes to Physician

Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Flammable Properties

NFPA: Class IIIB Combustible Liquid

5.1 Suitable Extinguishing Media:

Use extinguishing measures that are appropriate to local circumstances and the surrounding environment

Unsuitable Extinguishing Media:

Do not use a solid water stream as it may scatter and spread fire.

5.2 Specific Hazards Arising from the Chemical

Thermal decomposition can lead to release of irritating and toxic gases and vapors.

Hazardous combustion products:

During a fire, smoke may contain the original material in addition to combustion products of varying composition which may be toxic and / or irritating. Combustion products may include and are not limited to:

Carbon oxides
Calcium Oxides (CaOx)
Oxides of Magnesium
Nitrogen oxides (NOx)
Oxides of Phosphorus
Sulphur oxides
Zinc oxides

5.3 Protective Equipment and Precautions for Firefighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

6. ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures

Personal precautions

Avoid contact with eyes, skin and clothing. Avoid breathing vapors or mists. Use personal protection recommended in Section 8. Ensure adequate ventilation. Remove all sources of ignition.

6.2 Environmental Precautions

Environmental Precautions

See section 12 for additional ecological information. Prevent further leakage or spillage if safe to do so. Prevent product from entering drains. Do not allow material to contaminate ground water system. Do not flush into surface water or sanitary sewer system. Large Spills: Dike far ahead of liquid spill for later recovery and disposal. Prevent entry into waterways, sewers, basements or confined areas.

6.3 Methods and material for containment and cleaning up

Methods for Clean-up

Contain and collect spillage with non-combustible absorbent material, (e.g. sand, earth, diatomaceous earth, vermiculite) and place in container for disposal according to local / national regulations (see section 13).

Spill Management

LARGE SPILLS

Eliminate sources of ignition. Prevent additional discharge of material if possible to do so without hazard. For small spills implement cleanup procedures; for large spills implement cleanup procedures and, if in public area, keep public away and advise authorities. Also, if this product is subject to CERCLA reporting (see Section 15 Regulatory Information) notify the National Response Center.

WATER SPILLS

Prevent liquid entering sewers, watercourses, or low areas. Contain spilled liquid with sand

or earth. Recover by pumping or with suitable absorbent. If liquid is too viscous for pumping, scrape up. Consult an expert on disposal of recovered material and ensure conformity to local disposal regulations.

7. HANDLING AND STORAGE

7.1. Precautions for safe handling

Handling

Do not breathe dusts or mists. Avoid contact with eyes, skin and clothing. Wear protective gloves/protective clothing/eye protection/face protection. Use personal protection recommended in Section 8. Wash hands thoroughly after handling. Remove and wash contaminated clothing before re-use. Do not eat, drink or smoke when using this product. Should not be released into the environment.

Safe Handling Advice

Wear personal protective equipment. Do not breathe vapors or spray mist. Use product only in closed system.

7.2. Conditions for safe storage, including any incompatibilities

Storage

Keep in properly labeled containers. Keep container tightly closed in a dry and well-ventilated place.

Technical measures/Precautions

Ensure adequate ventilation. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded.

Incompatible Materials and/or Coatings

No information available

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters

Exposure Guidelines

Chemical Name	ACGIH TLV	OSHA PEL	Ontario TWAEV	Mexico	NIOSH IDLH
Methyl methacrylate	TWA: 50 ppm STEL: 100 ppm dermal sensitizer	TWA: 100 ppm TWA: 410 mg/m ³	STEL: 100 ppm TWA: 50 ppm	STEL: 125 ppm STEL: 510 mg/m ³ TWA: 100 ppm TWA: 410 mg/m ³	1000 ppm

Other Exposure Guidelines (If Generated)

Chemical Name	OSHA PEL	ACGIH TLV	ACGIH OEL (STEL)	NIOSH REL TWA	ILA IHG	ILA ROEG	ILA Internal Exposure Limit
Oil mist, mineral	TWA: 5 mg/m ³	TWA: 5 mg/m ³		TWA 5 mg/m ³ ST 10 mg/m ³			

8.2 Exposure controls

Appropriate engineering controls

Ensure adequate ventilation, especially in confined areas. Consider the potential hazards of this material (see Section 2), applicable exposure limits, job activities, and other substances in the work place when designing engineering controls and selecting personal protective

equipment. If engineering controls or work practices are not adequate to prevent exposure to harmful levels of this material, the personal protective equipment listed below is recommended. The user should read and understand all instructions and limitations supplied with the equipment since protection is usually provided for a limited time or under certain circumstances.

Personal Protective Equipment

Eye/face protection

Safety glasses equipped with side shields are recommended as minimum protection in industrial settings. If splashes are likely to occur wear tight fitting safety goggles and/or face-shield.

Skin protection

Wear protective gloves/clothing. Long sleeved clothing. Choose the appropriate protective clothing / gloves based on the tasks being performed to avoid exposed skin surfaces.

Glove Type: Neoprene, Nitriles

Respiratory protection

If exposure limits are exceeded or irritation is experienced, NIOSH/MSHA approved respiratory protection should be worn. Positive-pressure supplied air respirators may be required for high airborne contaminant concentrations. Respiratory protection must be provided in accordance with current local regulations.

General Hygiene Considerations

When using, do not eat, drink or smoke. Clean equipment, work area and clothing regularly.

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Appearance	Yellow / Clear
Physical State	Liquid
Odor	Mild
Odor Threshold	No information available
pH	Not applicable
Melting point / melting range	Not applicable
Boiling point / boiling range	No information available
Flash Point	> 170 °C / 338 °F COC ASTM D92
Evaporation Rate	No information available
Flammability Limit in Air	No information available
Explosion Limits	No information available
Vapor Pressure	No information available
Vapor Density (Air)	No information available
Density	0.86 g/cm ³ @15°C
Solubility	No information available
Partition Coefficient (n-octanol/water)	No information available
Autoignition Temperature	No information available
Decomposing Temperature	No information available
Viscosity	@ 40C = 47.72 cSt; @ 100C = 12.58 cSt

Other Information

No additional information available

10. STABILITY AND REACTIVITY

10.1 Reactivity

Reactivity

The product is chemically stable

10.2 Chemical stability

Chemical Stability

Stable under recommended storage conditions.

10.3 Possibility of Hazardous Reactions

Possibility of Hazardous Reactions

None under normal processing.

Hazardous Polymerization

Hazardous polymerisation does not occur.

10.4 Conditions to Avoid

Conditions to Avoid

To avoid thermal decomposition, do not overheat. Heat, flames and sparks.

10.5 Incompatible Materials

Incompatible Materials

Strong oxidizing agents.

10.6 Hazardous Decomposition Products

Hazardous decomposition products

Thermal decomposition can lead to release of irritating gases and vapors.

11. TOXICOLOGICAL INFORMATION

11.1 Information on likely routes of exposure

Inhalation	May cause respiratory irritation.
Eye contact	May cause slight irritation.
Skin Contact	May cause an allergic skin reaction.
Ingestion	May be harmful if swallowed.

Chemical Name	LD50 Oral	LD50 Dermal	LC50 Inhalation
Methyl methacrylate 80-62-6	= 7872 mg/kg (Rat) = 7900 mg/kg (Rat)	> 5 g/kg (Rabbit)	4632 ppm (Rat) 4 h

11.2 Information on toxicological effects

Symptoms	No information available
----------	--------------------------

11.3 Delayed and immediate effects as well as chronic effects from short and long-term exposure

Skin corrosion/irritation	Not classified.
Serious eye damage/eye irritation	Not classified.
Sensitization	May cause an allergic skin reaction.
Mutagenic effects	Not classified.

11.4 Carcinogenicity

Carcinogenicity	No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP, IARC, OSHA or ACGIH.
-----------------	--

Legend:

NTP (National Toxicology Program) ACGIH (American Conference of Governmental Industrial Hygienists) IARC (International Agency for Research on Cancer) OSHA (Occupational Safety and Health Administration of the US Department of Labor)

Reproductive Effects	Not classified.
----------------------	-----------------

STOT - single exposure Not classified.

STOT - repeated exposure Not classified

Aspiration hazard Not classified.

11.5 Acute Toxicity

Unknown acute toxicity 17.22 % of the mixture consists of ingredient(s) of unknown toxicity

The following values are calculated based on chapter 3.1 of the GHS document .

Product Information (Estimated):

ATEmix (oral) > 5,000 mg/kg

ATEmix (dermal) > 2,000 mg/kg

ATEmix (inhalation-dust/mist) > 5 mg/l

12. ECOLOGICAL INFORMATION

12.1 Ecotoxicity

Ecotoxicity effects

Harmful to aquatic life. Harmful to aquatic life with long lasting effects. Plants and animals may experience harmful or fatal effects when coated with petroleum products. Petroleum-based (mineral) lubricating oils normally will float on water. In stagnant or slow-flowing waterways, an oil layer can cover a large surface area. As a result, this oil layer might limit or eliminate natural atmospheric oxygen transport into the water. With time, if not removed, oxygen depletion in the waterway may be sufficient to cause a fish kill or create an anaerobic environment.

Unknown aquatic toxicity 24.23 % of the mixture consists of component(s) of unknown hazards to the aquatic environment

12.2 Persistence and degradability No information available.

12.3 Bioaccumulation/Accumulation

12.4. Mobility in soil No information available

PBT and vPvB assessment No information available

12.5 Other adverse effects:

Chemical Name	log Pow
Methyl methacrylate 80-62-6	0.7

13. DISPOSAL CONSIDERATIONS

Hazard characteristic and regulatory waste stream classification can change with product use. Accordingly, it is the responsibility of the user to determine the proper storage, transportation, treatment and/or disposal methodologies for spent materials and residues at the time of disposition.

Waste Disposal Method

This material, as supplied, is not a hazardous waste according to Federal regulations (40 CFR 261). This material could become a hazardous waste if it is mixed with or otherwise comes in contact with a hazardous waste, if chemical additions are made to this material, or if the material is processed or otherwise altered. Consult 40 CFR 261 to determine whether

the altered material is a hazardous waste. Consult the appropriate state, regional, or local regulations for additional requirements.

Contaminated packaging Dispose of in accordance with local regulations.

Chemical Name	RCRA
Methyl methacrylate (CAS #: 80-62-6)	U162 Ignitable waste, Toxic waste Included in waste stream: F039 Present U162 0.14 mg/L wastewater 160 mg/kg nonwastewater

14. TRANSPORT INFORMATION

DOT - Non bulk Not regulated

DOT - Bulk Not regulated

IATA Not regulated

IMDG/IMO Not regulated

15. REGULATORY INFORMATION

International Inventories

TSCA	All ingredients are on the inventory or exempt from listing
DSL	All ingredients are on the inventory or exempt from listing
NDSL	Not Listed
ELINCS	Not Listed
ENCS	All ingredients are on the inventory or exempt from listing
CHINA	All ingredients are on the inventory or exempt from listing
KECL	All ingredients are on the inventory or exempt from listing
PICCS	All ingredients are on the inventory or exempt from listing
AICS	All ingredients are on the inventory or exempt from listing
NZIoC	All ingredients are on the inventory or exempt from listing
REACH	All ingredients are on the inventory or exempt from listing

USA

Federal Regulations

SARA 313

Section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product does not contain any chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 372

SARA 311/312 Hazardous Categorization

Acute Health Hazard	Skin Sensitizer
Chronic Health Hazard	Skin Sensitizer
Fire Hazard	No
Sudden Release of Pressure Hazard	No
Reactive Hazard	No

CERCLA/SARA 302 & 304

Section 302 & 304 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA). This product contains chemicals which are subject to the reporting requirements of the Act and Title 40 of the Code of Federal Regulations, Part 355.

Chemical Name	CAS No.	Weight-%	RQ	TPQ
Methyl methacrylate	80-62-6	<1	1000 lb final RQ 454 kg final RQ	
Aniline	62-53-3	<0.001	5000 lb final RQ 2270 kg final RQ	1000 lb TPQ
.alpha.-Naphthylamine	134-32-7	<0.0001	100 lb final RQ 45.4 kg final RQ	
.beta.-Naphthylamine	91-59-8	<0.00001	10 lb final RQ 4.54 kg final RQ	
Lead	7439-92-1	<0.00001	10 lb final RQ 4.54 kg final RQ	
Arsenic	7440-38-2	<0.00001	1 lb final RQ 0.454 kg final RQ	
Cadmium	7440-43-9	<0.00001	10 lb final RQ 4.54 kg final RQ	

Clean Air Act, Section 112 Hazardous Air Pollutants (HAPs) (see 40 CFR 61)

This product contains the following HAPs:

Chemical Name	CAS No.	Weight-%	HAPS data
Methyl methacrylate	80-62-6	<1	X
Aniline	62-53-3	<0.001	X

CWA (Clean Water Act)

This product contains the following substances which are regulated pollutants pursuant to the Clean Water Act (40 CFR 122.21 and 40 CFR 122.42)

Chemical Name	CAS No.	Weight-%	U.S. - CWA (Clean Water Act)
Phosphorodithioic acid, O,O-di-C1-14-alkyl esters, zinc salts	68649-42-3	<1	X
Methyl methacrylate	80-62-6	<1	X
Aniline	62-53-3	<0.001	X
Lead	7439-92-1	<0.00001	X
Arsenic	7440-38-2	<0.00001	X
Cadmium	7440-43-9	<0.00001	X

State Regulations

California Proposition 65



This product can expose you to chemicals including, [Aniline, .alpha.-Naphthylamine, .beta.-naphthylamine, Lead, Arsenic, Cadmium], which are known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov

Chemical Name	CAS No.	Weight-%	California Prop. 65	Maximum Allowable Dose for Reproductive Toxicity (MADLS)	Safe Harbor Limits for Cancer-causing Chemicals (NSRLs)
Aniline	62-53-3	<0.001	Carcinogen		100 µg/day
.alpha.-Naphthylamine	134-32-7	<0.0001	Carcinogen		

.beta.-Naphthylamine	91-59-8	<0.00001	Carcinogen		0.4 µg/day
Lead	7439-92-1	<0.00001	Carcinogen Developmental Female Reproductive Male Reproductive	0.5µg/day	15 µg/day oral
Arsenic	7440-38-2	<0.00001	Carcinogen		0.06 µg/day inhalation 10 µg/day except inhalation
Cadmium	7440-43-9	<0.00001	Carcinogen Developmental Male Reproductive	4.1µg/dayoral	0.05 µg/day inhalation

State Right-to-Know

Chemical Name	CAS No.	New Jersey
distillates (petroleum), hydrotreated light paraffinic	64742-55-8	X
Petroleum distillates, solvent dewaxed heavy paraffinic	64742-65-0	X
Petroleum distillates, hydrotreated heavy paraffinic	64742-54-7	X
Amines, polyethylenepoly-, reaction products with succinic anhydride polybutenyl derivatives	68439-80-5	X
Petroleum distillates, solvent-refined heavy paraffinic	64741-88-4	X
Petroleum distillates, solvent-refined light paraffinic	64741-89-5	X
Petroleum distillates, solvent dewaxed light paraffinic	64742-56-9	X
Methyl methacrylate	80-62-6	X

Chemical Name	CAS No.	Massachusetts
distillates (petroleum), hydrotreated light paraffinic	64742-55-8	X

Chemical Name	CAS No.	Pennsylvania
distillates (petroleum), hydrotreated light paraffinic	64742-55-8	X
Petroleum distillates, solvent dewaxed heavy paraffinic	64742-65-0	X
Amines, polyethylenepoly-, reaction products with succinic anhydride polybutenyl derivatives	68439-80-5	X

New Jersey Worker and Community Right-to-Know Act:

Under the New Jersey Right-to-Know Act L. 1983 Chapter 315 N.J.S.A. 34:5A-1 et. seq., the product is to be identified as follows:
PETROLEUM OIL (Lubricating Oil)

Canada

This material has been classified in accordance with the WHMIS 2015 regulation


Chemical Name	CAS No.	Weight-%	NPRI
distillates (petroleum), hydrotreated light	64742-47-8	<1	Listed
Methyl methacrylate	80-62-6	<1	Listed
Trade Secret	Confidential	<0.1	Listed
Solvent naphtha (petroleum), medium aliphatic	64742-88-7	<0.01	Listed
Aniline	62-53-3	<0.001	Listed

Lead	7439-92-1	<0.00001	Listed
Arsenic	7440-38-2	<0.00001	Listed
Cadmium	7440-43-9	<0.00001	Listed

Legend

NPRI - National Pollutant Release Inventory

16. OTHER INFORMATION



NFPA

Health: 2

Flammability: 1

Instability: 0

Prepared By

Lakyn Neumeyer

Revision Date:

24-May-2017

Revision Summary:

New product number

Disclaimer:

The information provided on this SDS is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guide for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered as a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other material or in any process, unless specified in the text.

End of Safety Data Sheet