INSTALLATION INSTRUCTIONS

Accessory


ROOF CARRIER

Application

2023 HR-V MODEL SERIES Publications No. VERSION 1

Issue Date
MAY 2022

GENERAL VIEW



FOR YOUR SAFETY (Read carefully.)

Warning Symbols

Safety: Your safety, and the safety of others, is important. To help you make informed decisions about service procedures, we have provided safety messages where appropriate. Of course, it is not practical or possible to warn you about all the hazards associated with servicing a vehicle - you must use your own good judgment.

You will find important safety messages preceded by one of following symbols:

^{*}All symbols are not used in all installation instructions.

▲ DANGER	You will be killed or seriously hurt if you do not follow the instructions.
A WARNING	You can be killed or seriously hurt if you do not follow the instructions.
▲ CAUTION	You can be hurt if you do not follow the instructions.
NOTICE	Gives advice to prevent damage to the product, vehicle, the environment or other property.
NOTE	Gives helpful information or instructions to be followed when installing this product.



Indicates a prohibited action.

Procedure and Location Icons

These icons indicate the work location and the worker's point of view.

*All icons are not used in all installation instructions.



The location on the vehicle.



The location in the vehicle. (instrument panel.)



Wear eye protection.



Wear heavy gloves.



Use an assistant.



Place the part on a blanket.



Work perpendicular.



Remove any burrs.



Use touch-up paint and allow to dry.



Tighten to the specified torque.



Apply firm pressure while rolling, especially at the ends, to set the adhesive.



Press firmly.



Clean with isopropyl alcohol.



Return the original part to the customer. (Do not reuse.)

Safety: General


- Be careful not to damage the vehicle or the parts.
- The illustrations may differ slightly from the actual accessory.

Safety: Accessory

Always use the parts and tools specified in the installation instructions.

PARTS LIST

Roof Carrier Kit (P/N 08L02-3V0-100)





REQUIRED TOOLS AND SUPPLIES

Utility knife

INSTALLATION

1. Remove the covers.






2. Install the cushions.

NOTE


Make sure to check the labels and identification marks before installation.




Install the slot covers.

NOTE

Cut-off the excess slot cover material if needed.



4. Loosen the socket bolts.




5. Position the roof carriers.

NOTE

Make sure to check the labels before installation.

6. Loosely tighten the socket bolts.




7. Secure the roof carriers.

NOTE

- Make sure that there are no gaps between the roof and cushions.
- Tighten the left and right socket bolts alternately to evenly distribute the pressure.
- Tighten the left and right socket bolts until you hear a clicking sound.
- 8. Ensure the roof carriers are firmly secured.

NOTE

- Make sure that there are no gaps between the roof and cushions.
- Rock the roof carriers in all directions to check if they are installed securely without play or rattle.
- If the roof carriers have abnormal play or rattle, retighten the socket bolts, or reinstall the roof carriers as described in these installation instructions.



9. Install the covers.

ROOF


CUSHION

NOTE


Make sure to check the identification marks before installation.

SECTION VIEW


QL52807AG



10. Confirm the covers are locked.



11. Write down the key number.



QL92010AH

- 12. Check that all parts are installed properly.
- Give the Accessory User's Information Manual to the customer.